



GEAR OIL 140 API GL-5

CORAL OIL SAE 140 API GL5- Gear Oil is a high-viscosity lubricant Formulated Primarily For Heavy-duty Machinery and automotive applications That Require a thicker Oil to Handle Extreme Pressure high load, and Slow-speed Conditions It is typically rated API GL5-, Which Ensures it is Designed to Meet the Stringent Requirements of Extreme Pressure Protection Making it Suitable for use in Differentials, Transmissions, and Other Gear Systems.

SPECIFICATIONS AND MEETS:

API GL5-, MIL-L2105-D, ZF TE-ML 05A CS 3000B,

Ford M2C9002-A, Mack GO-G

GM 1899M, GM 93740141, GM

Packaging: 1 Litre / 4 Litres / 5 Litres / 25 Litres / 208 Litres

| PROPERTY | VALUE | TEST METHOD |
|-------------------|-------------------------|-------------|
| Appearance | Clear liquid | VISUAL |
| Density @ 15°C | 0.895 g/cm ³ | ASTM D4052 |
| Viscosity @ 40°C | 422 cSt | ASTM D445 |
| Viscosity @ 100°C | 29 CSt | ASTM D445 |
| Viscosity Index | 96.28 | ASTM D2270 |
| Pour Point | -12 °C | ASTM D97 |
| Flash Point (COC) | 243°C | ASTM D92 |

BENEFITS

- Highest pressure-absorption capability
- Wear reduction
- Noise reduction
- Excellent viscosity/temperature properties
- Excellent ageing resistance
- All sealing materials compatibilist

APPLICATIONS

- Highest pressure-absorption capability
- Wear reduction
- Noise reduction
- Excellent viscosity/temperature properties
- Excellent ageing resistance
- All sealing materials compatibilist