



GEAR OIL 150 GL-5

CORAL OIL SAE 150 Gear Oil is a high-viscosity lubricant Designed For use in heavy-duty applications that Require higher load-bearing Capacity, low-Speed, and high-torque Conditions It is Particularly Useful For industrial Gear Systems, Differentials, and Manual Transmissions That Experience Extreme Pressure and Require Superior Wear Protection.

SPECIFICATIONS AND MEETS:

API GL-5, AGMA 9005-F16, DIN 51517-3:2018-09,
ISO L-CKD (ISO 12925-1:2024)
L-CTPR (ISO 12925-1:2024)

Packaging: 1 Litre / 4 Litres / 5 Litres / 25 Litres / 208 Litres

PROPERTY	VALUE	TEST METHOD
Appearance	Clear liquid	Visual
Density @ 15°C	0.88 g/cm ³	ASTM D4052
Viscosity @ 40°C	156 cSt	ASTM D445
Viscosity @ 100°C	15.6 CSt	ASTM D445
Viscosity Index	101.9	ASTM D2270
Pour Point	-20 °C	ASTM D97
Flash Point (COC)	200 °C	ASTM D92

BENEFITS

- Extreme Pressure (EP) Protection • Superior Wear Resistance
- Oxidation & Thermal Stability • Corrosion & Rust Protection
- Foam Suppression

APPLICATIONS

- Automotive Differentials • Manual Transmissions
- Heavy-Duty Equipment • Agricultural Machinery