



BASIC SCOOTER - MINERAL OIL

API TC • ISO L-EGB • JASO FB

2T MOTORBIKE

High-quality Mineral-based Engine Oil Specially Developed For 2-Stroke Ccooter Engines. Provides Reliable Lubrication, Effective Deposit Control, and Smooth Engine Operation For Everyday urban Riding.

PROPERTY	VALUE
SAE Grade	2T
Viscosity @ 40°C (mm ² /s)	60.2 mm ² /s
Viscosity @ 100°C (mm ² /s)	9.01 mm ² /s
Viscosity Index	130
Pour Point (°C)	≤ -15°C
Flash Point (°C)	≥ 220°C
Density @ 15°C (g/cm ³)	0.874 g/cm ³
Total Base Number (TBN, mg KOH/g)	7–9 mg KOH/g

SPECIFICATIONS AND APPROVALS:

•API TC • JASO FB

OEM APPROVALS:

Formulated to Meet The Performance Requirements of 2-stroke Scooter Manufacturers Specifying API TC And JASO FB Performance Levels.

BENEFITS

- Reliable lubrication for Daily Commuting.
- Helps Reduce Exhaust Smoke.
- Protects against Piston Scuffing and Wear.
- Maintains Engine Cleanliness.
- Stable Performance in Stop-and-go traffic Conditions.

APPLICATIONS

- Recommended for 2-Stroke Scooters With Oil injection Systems Or pre-Mix Lubrication, Operating Under Normal City Riding Conditions.

