



CORAL HEXOGEN (SAE 10W-30)

CORAL HEXOGEN 10W-30 is API SQ , ILSAC GF-7A Motor oil Developed With advanced Molybdenum-based friction Control Technology Designed to Provide Superior Protection for Modern Gasoline and light-duty Diesel Engines, it Ensures improved fuel Economy Exceptional Engine Cleanliness, and long-lasting Wear Protection The Distinctive Green Color Simplifies Maintenance by Enabling quick identification of Leaks.

| PROPERTY | VALUE |
|--|--------|
| SAE Grade | 10W-30 |
| Viscosity @ 40°C (mm ² /s) | 66.9 |
| Viscosity @ 100°C (mm ² /s) | 11.0 |
| Viscosity Index | 157 |
| Pour Point (°C) | -42 |
| Flash Point (°C) | 224 |
| Density @ 15°C (g/cm ³) | 0.871 |
| Evaporation Loss (Noack) (%) | 10.0 |
| HTHS Viscosity @ 150°C (mPas) | ≥3.0 |
| Sulfated Ash (%) | ≤0.8 |
| Total Base Number (TBN, mg KOH/g) | 7.1 |

SPECIFICATIONS AND APPROVALS:

- API: SQ
- ILSAC: GF-7A
- ACEA: A3/B4

OEM APPROVALS:

- Ford: WSS-M2C946-A
- Chrysler: MS-6395
- General Motors: dexos1™ Gen 2

BENEFITS

- Advanced Friction Reduction: Molybdenum-based additives significantly decrease friction, enhancing efficiency.
- Wear Protection: Provides robust anti-wear properties, ensuring long-lasting engine protection.
- Fuel Economy: Low viscosity formulation improves fuel efficiency and reduces CO₂ emissions.
- Leak Detection: Green coloration facilitates quick identification of leaks during maintenance.
- Emission Compatibility: Protects catalytic converters and supports emission control systems.
- Cold Start Performance: Ensures rapid lubrication and engine protection in cold weather.

APPLICATIONS

- Suitable for Gasoline Engines: Meets API SQ and ACEA A3/B4 standards for Modern Gasoline Engines including Turbocharged and Direct-injection Systems.
- Light-Duty Diesel Engines: Compatible With Passenger car diesel engines where ACEA A3/B4 is specified.
- Hybrid Vehicles: Suitable for hybrid Gasoline Engines requiring 10W-30 viscosity and API SP Standards.