



SAE 10W-40 API SP – JASO MA2 SYNTHETIC TECHNOLOGY

4T MOTORBIKE

High-Performance Engine Oil Formulated With advanced Synthetic Technology Base Oils and Modern Additive Systems Designed to Provide Excellent Protection improved Engine Cleanliness and Stable Viscosity Under Demanding Operating Conditions Suitable for Modern 4-Stroke Motorcycle Engines Requiring JASO MA2 Specification.

PROPERTY	VALUE
SAE Grade	10W-40
Viscosity @ 40°C (mm ² /s)	110 mm ² /s
Viscosity @ 100°C (mm ² /s)	14.3 mm ² /s
Viscosity Index	128.77
Pour Point (°C)	≤ -15°C
Flash Point (°C)	≥ 230°C
Density @ 15°C (g/cm ³)	0.867 g/cm ³
Total Base Number (TBN, mg KOH/g)	7–9 mg KOH/g

SPECIFICATIONS AND APPROVALS:

• API SP • JASO MA2

OEM APPROVALS:

Formulated to Meet the Performance Requirements of leading international Motorcycle Manufacturers Requiring SAE 10W-40, API SP, JASO MA2 Specifications.

BENEFITS

- Excellent Engine Protection against Wear and Deposits.
- Superior thermal and Oxidation Stability.
- Smooth Clutch Performance With JASO MA2 Wet clutch Compatibility.
- Reliable lubrication at high Temperatures and heavy loads.
- Helps maintain Engine Cleanliness and Performance.

APPLICATIONS

Recommended For high-performance Motorcycles, including Engines With Wet clutch Systems, Operating under Both Normal and severe Riding Conditions Suitable for air-cooled and liquid-cooled Engines.

